



OHIO'S LEADING SOURCE FOR CERTIFIED "GREEN" PRODUCTS

## ENVIRONMENTALLY "GREEN"

- FSC CERTIFIED
- NO ADDED UREA FORMALDEHYDE
- C.A.R.B II.- (CALIFORNIA AIR RESOURCES BOARD) – MEETS FORMALDEHYDE EMISSION STANDARDS

## HARDWOOD PLYWOODS

### DOMESTIC

- FSC CERTIFIED
- NO ADDED UREA FORMALDEHYDE
- SPECIES: RED OAK, BIRCH, CHERRY, MAPLE, ASH, POPLAR, HICKORY, QTR. WHITE OAK, MAHOGANY, WALNUT
- FXP: MDF FACE AND BACK
- MULTICORE
- PERFORMANCE CORE
- VENEER CORE (7-PLY) ASPEN AND POPLAR AVAILABLE
- MDF CORE
- PARTICLEBOARD CORE IPB
- ARCHITECTURAL GRADE PANELS
- PREFINISHED 1 & 2 SIDE
- BENDING PLYWOOD DOMESTIC 4X8 (COLUMN) & 8X4 (BARREL) 5.2MM, 9.0MM, 15.0MM
- SHOP DOWN FALL
- BEADED PANELS
- ECONOMY HARDWOOD PANELS
- HARDWOOD CRATING PANELS
- 5/32" – 2" THICKNESS AVAIL.
- 4' & 5' WIDE AVAIL.
- 6', 8', 10' & 12' LENGTHS AVAIL.
- FIRE RATED (RETARDANT)

### IMPORT PLYWOODS

- C.A.R.B. II COMPLIANT
- LITEWEIGHT ITALIAN POPLAR 4'X8', 5'X8' & 6'X8' AVAIL
- RUSSIAN BIRCH 5X5 & 4X8
- BAMBOO
- MERANTI/LAUAN/OKUME
- 3MM – 25MM THICKNESS AVAIL.

## ENGINEERED WOOD COMPOSITES

### MDF

- FSC CERTIFIED
- NO ADDED UREA FORMALDEHYDE
- C.A.R.B II.
- BLACK DIAMOND MDF
- ULTRA LITEWEIGHT
- MOISTURE RESISTANCE
- FIRE RETARDANT
- OVERSIZED PANELS
- THICKNESS 1/8" THROUGH 2"
- MOULDING BLANKS UP 16'

### PARTICLEBOARD

- FSC CERTIFIED
- NO ADDED UREA FORMALDEHYDE
- C.A.R.B II.
- FIRE RATED (RETARDANT)
- LITEWEIGHT
- MOISTURE RESISTANT
- FIRE RETARDANT
- UNDERLAYMENT
- M2 & M3 PROPERTIES
- THICKNESS 1/4" THROUGH 2"

### EXTERIOR GRADE FIBERBOARD

- FORMALDEHYDE FREE
- MDO REPLACEMENT
- THICKNESS: 1/2" THROUGH 1 1/4"
- 4X8, 4X16, 25"X16' PANELS
- MOULDING BLANKS AVAILABLE
- ANY EXTERIOR APPLICATION

### HARDBOARD

- NO ADDED UREA FORMALDEHYDE
- TEMPERED
- PAINTED
- S2S / PERFORATED

### MELAMINE

- FSC CERTIFIED
- NO ADDED UREA FORMALDEHYDE
- FIRE RATED (RETARDANT)
- PARTICLEBOARD AND MDF
- LIGHT WEIGHT VENEER CORE

## LUMBER

### HARDWOOD

- 4/4 THROUGH 8/4
- RED OAK, POPLAR, CHERRY, HARD MAPLE, SOFT MAPLE, ASH, SAPELLI, ALDER
- MILLING AVAILABLE

### SOFTWOOD

- CLEAR VERTICAL GRAIN DOUG FIR
- A&BTR WESTERN RED CEDAR
- PONDEROSA PINE
- EASTERN WHITE PINE

## SOFTWOOD PLYWOODS

- FSC / FORMALDEHYDE FREE
- FIRE RETARDANT PANELS
- AC, BC, SANDED SYP, FIR AND CHILEAN PINE, MARINE GRADE
- RATED SHEATHING

### HDF EXTERIOR ULTRA CORE

- PAINT AND LAMINATE GRADE
- LIGHT WEIGHT
- SOLID COMPOSED EXT. CORE

## CONSTRUCTION AND PACKAGING

- FSC CERTIFIED
- NO ADDED UREA FORMALDEHYDE
- OSB, RATED SHEATHING, CDX, UTILITY / SHOP GRADE SYP.
- LITEWEIGHT PANELS.
- DIMENSIONAL 2BY SPF, SYP

## ADDITIONAL SERVICES

- HIGH PRESSURE / VERTICAL GRADE LAMINATING
- VINYL / FOIL LAMINATING
- CUT TO SIZE PANELS
- MILLWORK CAPABILITY
- PAINT AND PRIMING

WE GUARANTEE OUR SERVICE AND PRODUCTS 100%

AKRON/CANTON\*\*\*CINCINNATI\*\*\*CLEVELAND\*\*\*COLUMBUS\*\*\*DAYTON\*\*\*TOLEDO  
TOLL FREE – 877-200-4213 / 614-545-5390 / FAX 614-491-4423

[WWW.PACKARDFORESTPRODUCTS.COM](http://WWW.PACKARDFORESTPRODUCTS.COM)